

Model No. CK2007	High Tenacity Polyester PVC Laminated Fabrics
General Applications:	Construction, Marine (Field) covers, Storage covers and many other applications
Type of Products:	Roll Type – 2Mx45M, Color: Green, White, Grey, Blue
	Roll Type – 2.5Mx45M, Color: Green, White
Thickness:	0.3mm
Available Grades:	Fire-Retardant, Ultra-Violet, Anti-Mildew, Anti-Cold
Flammability Test Method:	BS5867-2:2008 - Flammability



抗水
Water
Resistant



不變形
Dimensional
Stability



阻燃
Flame
Retardant



長壽命
Long
Lasting



抗紫外線
UV
Resistant



色牢度
Color
Fastness

Physical Properties:

SPGL: 280g

性能 Properties	測試方法 Test Method	單位 Unit	結果 Result	
基布材質 Basic Fabric Material	----	----	聚酯纖維 Polyester	
基布類型 Type of Basic Fabric	----	----	2020-18*12	
塗層類型 Type of Coating	----	----	E-PVC	
厚度 Thickness	DIN 53353	mm	0.25-0.3	
重量 Weight	DIN 53352	g/m ²	280	
拉力強度 Tensile Strength	DIN 53354	N/5cm	經: 548	緯: 265
撕裂強度 Tear Strength	DIN 53363	N	經: 119	緯: 107
剝離強度 Adhesion	DIN 53357	N/5cm	18	
使用溫度 Operating Temp	-20 ~ 70 °C		(-4 ~ 160 °F)	
選項 Option	<input checked="" type="checkbox"/> 阻燃 Flame Retardant <input type="checkbox"/> 防霉 Anti-Mildew <input type="checkbox"/> 防紫外線 U. V. Resistance <input type="checkbox"/> 耐寒 Cold Resistance <input type="checkbox"/> 表面處理 Surface Treatment			
備注 Remark	1. 誤差: 正負 10%, 試驗均值; 2. 以上數據是出廠時的檢測值, 本產品會隨長時間儲存或使用後, 某些性能會衰減, 實測數據會有所降低			

This technical data is offered as helpful suggestion only.

It's accurate to the best of our knowledge at time of printing.